



suitable for transferring, Spraying of Lubricating, Rust Proof, Undercoating Fluids (oil, Grease, Wax, Glue etc.)

FEATURES

- Pneumatically sensed air motor
- Double acting pulsation Free output (suitable for spraying)
- Stainless steel rust proof hydraulic body
- Easy maintenance
- Ice free motors
- Light & easy to handle

Technical Specifications

Type	Hippo 5.230	Hippo 10.230	Hippo 20.230
Pressure Ratio	5 :1	10 :1	20 :1
Out put per Cycle	230 cc	230 cc	230 cc
Air motor Piston Ø	80 mm	110 mm	160 mm
Stroke Length	120 mm	120 mm	120 mm
Recommended Transfer Volume per minute	11.5 ltr.	9.2 ltr.	6.9 ltr.
Air Inlet Pressure Max.	8 bar	8 bar	8 bar
Outlet Pressure Max.	40bar	80 bar	160 bar
Air Consumption N liter/min Max.	480	730	1150
Typical fluids handled	Motor oil, Synthetic oil, Hydraulic oil, Auto transmission fluid	Motor oil, Synthetic oil, Gear oil, pourable Light lubricating grease	Under coating/rust proofing fluids. pourable lubricating grease, pourable Glues, Pastes

ACCESSORIES

- Manual /Automatic
- Guns with flow indicators
- Guns with batch controller
- Hose Reals
- Lifters
- Barrel covers

For other High Volume & Bulk Handling of Grease & Oil, please refer other range of equipments, i.e. DRUM PRESS, RHINO, TIGER, ELEPHANT etc.