



# CUB

## FOUR BALL PISTON PUMP

*The range is suitable for transferring paints materials, Oils, explosive liquids, feed multiple spray guns and paints circulation systems. It is design for for high delivery upto 16 ltr/min.*

### FEATURES

- Low shear out put.
- Very less & easy maintenance.
- Compact & easy assembly.
- Hard coated piston & cylinder.
- Very less wear & tear.
- Long life small throat seal stuffing- fast & easily replaceable.

ALLUMINIUM & STAINLESS STEEL WET PART  
VERSIONS



### TECHNICAL SPECIFICATIONS

Type	CUB 2.240	CUB 2.400	CUB 6.400
Ratio	2:1	2:1	6:1
Output per Cycle	240 cc	400 cc	400 cc
Air Motor Piston Ø	80 mm	80 mm	125 mm
Stroke Length	70mm	120mm	120mm
Output at 25 cycles	6ltrs.	10ltrs.	10ltrs.
Air Inlet Pressure Max.	6 bar	6 bar	4 bar
Output Pressure Max.	12 bar	12 bar	24 bar
Air consumption N liter/min @ 25 cycles.	106	181	300



## VR COATINGS PVT.LTD.

J-138,MIDC PUNE – 411 026,INDIA.

TEL: (020)27122331, 27121890 FAX : (020) 27121891,27495273

E-MAIL: sales@vrcoatings.com,vrcoatings@eth.net . Web : www.vrcoatings.com

