



DRUM PRESS

MEDIUM & HEAVY DUTY AIRLESS DRUM PRESS DISPENSING/ SPARYING PAINTING EQUIPMENT

These are equipped with medium duty (TIGER) or heavy duty (RHINO) range of pumps and are suitable for semi-solid and pasty materials

FEATURES

- High flow rate pumps and guns
- Priming piston (shovel) type. Suction for high viscosity fluid
- Auto shut off for pumps
- Facility for twin pail switchover system
- Drum capacity upto 200 ltr.
- Custom built system for more drum capacity with special features.
- Dispensing / spraying nozzles to suit your application



TECHNICAL SPECIFICATIONS

Type	30.150D	35.275D	40.110D	55.275D	75.210D
Ratio *	30:1	35:1	40:1	55:1	75:1
Output per Cycle	150cc	275cc	110cc	275cc	210cc
Air Motor Piston Ø	160 mm	250 mm	160 mm	300 mm	300 mm
Stroke Length	120 mm	120 mm	120 mm	120 mm	120 mm
Recommended Spray volume at 10 cycles per minute.	1.5 liters	2.75 liters	1.1 liters	2.75 liters	2.1 liters
Air Inlet Pressure Maximum.	6bar	7 bar	6 bar	6bar	6 bar
Output Pressure Maximum.	180 bar	245 bar	240 bar	330 bar	450 bar
Air consumption N liter per min at 10 cycle per minute.	300	850	300	1100	1100

* Other ratios and outputs on request



VR COATINGS PVT.LTD.

J-138,MIDC PUNE – 411 026,INDIA.

TEL: +91 (020) 30781022, 27130331 FAX : +91 (020) 30781051, 27495273

E-MAIL: vrcoatings@eth.net sales@vrcoatings.com. Web : www.vrcoatings.com

