



ELEPHANT

LOW PRESSURE PAINT TRANSFER PUMPS

The range is suitable for transferring paints materials, Oils, explosive liquids, feed multiple spray guns and paints circulation systems. It is design for for high delivery upto 120 ltr/min. and more.

FEATURES

- Pneumatically sensed Air Motor.
- High Flow Rate-Four Ball Pump
- Stainless Steel rust proof Hydraulic Body
- Easy Maintenance
- Ice Free Air Motors
- Non turbulent flow suitable for metallic and water borne paints.



TECHNICAL SPECIFICATIONS

Type	2.4000	2.6500	3.2000	2.2000
Ratio *	2:1	2:1	3:1	2:1
Output per Cycle	4000 cc	6500 cc	2000 cc	2000 cc
Air Motor Piston Ø	250mm	250mm	200mm	160mm
Stroke Length	120 mm	200 mm	120 mm	120 mm
Transfer volume @ 20 cycles/min	80 liters	130 liters	40 liters	40liters
Air Inlet Pressure Maximum.	6 bar	6 bar	6 bar	6 bar
Output Pressure Maximum.	12 bar	12 bar	18 bar	12 bar
Air consumption N liter /min at 20 cycles.	1450	2400	910	600

* Other higher ratios on request



VR COATINGS PVT.LTD.

J-138,MIDC PUNE – 411 026,INDIA.

TEL: (020)27122331, 27121890 FAX : (020) 27121891,27495273

E-MAIL: sales@vrcoatings.com,vrcoatings@eth.net . Web : www.vrcoatings.com

