



HIPPO

LOW & MEDIUM DUTY AIRLESS SPARY PAINTING EQUIPMENT

The range is suitable for transferring paints materials, Oils, explosive liquids, feed multiple spray guns and paints circulation systems. It is design for for high delivery upto 30 ltr/min.

FEATURES

- Pneumatically sensed air motor
- High Flow Rate
- Stainless Steel rust proof Hydraulic body
- Easy maintenance
- Ice free motors.
- Light & Easy to Handle.



TECHNICAL SPECIFICATIONS

Type	1:170	3:400	3:900	5:900
Ratio	1:1	3:1	3:1	5:1
Output per Cycle	170cc	400cc	900cc	900cc
Air Motor Piston Ø	-	80 mm	125 mm	160 mm
Stroke Length	-	120 mm	120 mm	120 mm
Recommended Transfer volume per minute at 25 cycles	4.25 liters	10 liters	22.5 liters	22.5 liters
Air Inlet Pressure Maximum.	6 bar	6 bar	6 bar	6 bar
Output Pressure Maximum.	6 bar	18 bar	18 bar	30bar
Air consumption N liter/min Maximum at 25 cycles.	30	181	450	750



VR COATINGS PVT.LTD.

J-138,MIDC PUNE – 411 026,INDIA.

TEL: (020)27122331, 27121890 FAX : (020) 27121891,27495273

E-MAIL: sales@vrcoatings.com, vrcoatings@eth.net . Web : www.vrcoatings.com

