



RHINO

HEAVY DUTY AIRLESS SPARY PAINTING EQUIPMENT

The range is designed for tough working conditions and Suitable for High viscosity, solventless, low solvent coating, semisolid coating, marine coating, etc.

FEATURES

- Pneumatically sensed high performance Air Motor
- High Flow Rate
- Stainless Steel / Rust proof Hydraulic body
- Easy maintenance
- Ice free motors
- Light & Easy to Handle
- Compliance to EEC Norms



TECHNICAL SPECIFICATIONS

Type	35.275	50.210	55.275	60.180	75.210
Ratio	35:1	50:1	55:1	60:1	75:1
Output per Cycle	275cc	210cc	275cc	180cc	210cc
Air Motor Piston Ø	250 mm	250 mm	300 mm	250 mm	300 mm
Stroke Length	120 mm	120 mm	120 mm	120 mm	120 mm
Recommended Spray volume at 25 cycle per minute.	6.8 liters	5.25 liters	6.8 liters	4.5 liters	5.25 liters
Air Inlet Pressure Maximum.	7 bar	7 bar	7 bar	7 bar	6 bar
Output Pressure Maximum.	245 bar	350 bar	385 bar	420 bar	450 bar
Air consumption N liter per min at 25 cycle per minute.	2100	2100	2700	2100	2700



VR COATINGS PVT.LTD.

J-138, MIDC PUNE – 411 026, INDIA.

TEL: +91 (020) 30781022, 27130331 FAX : +91 (020) 30781051, 27495273

E-MAIL: vrcoatings@eth.net sales@vrcoatings.com. Web : www.vrcoatings.com

