



TIGER

LOW & MEDIUM DUTY AIRLESS SPARY PAINTING EQUIPMENT

The range is suitable for liquids of medium viscosities, primers, finish paints and paints of medium viscosity & particle size.

FEATURES

- Pneumatically sensed air motor
- High Flow Rate
- Stainless Steel / Rust proof Hydraulic body.
- Easy maintenance
- Ice free motors..
- Light & Easy to Handle.



TECHNICAL SPECIFICATIONS

Type	16.150	28.40	30.150	35.70	40.110	45.150	60.110
Ratio	16:1	28:1	30:1	35:1	40:1	45:1	60:1
Output per Cycle	150cc	40cc	150cc	70cc	110cc	150cc	110cc
Air Motor Piston Ø	125 mm	80 mm	160 mm	125 mm	160 mm	200 mm	200mm
Stroke Length	120 mm	120 mm	120 mm	120 mm	120 mm	120 mm	120mm
Recommended Spray volume at 25 cycles per minute.	3.75 liters	1 liters	3.75 liters	1.75 liters	2.75 liters	3.75 liters	2.75 liters
Air Inlet Pressure Maximum.	8bar	6 bar	8 bar	6 bar	8 bar	6 bar	6 bar
Output Pressure Maximum.	128 bar	168 bar	240 bar	210 bar	320 bar	270 bar	360bar
Air consumption N liter per min at 25 cycle .	600	200	1000	450	1000	1150	1150



VR COATINGS PVT.LTD.

J-138,MIDC PUNE – 411 026,INDIA.

TEL: +91 (020) 30781022, 27130331 FAX : +91 (020) 30781051,27495273

E-MAIL:,vrcoatings@eth.net , sales@vrcoatings.com. Web : www.vrcoatings.com

